

# GenieMaster™ TRANSMITTER OPERATION

### A. For use with Intellicode® 1 Openers—

The Universal Remote comes from the factory in the Intellicode® 1 Operating Mode. The Intellicode® 1 Mode is indicated by a RED LED on the remote whenever a button is pressed (FIG. 2).

Program it as you would any *Intellicode® 1* remote using the following steps:

- 1. Locate the Learn Code Button and Learn Code Indicator LED on your opener's powerhead (FIG. 1) (See owner's manual).
- 2. Press and release the Learn Code Button—the Learn Code LED will blink rapidly.
- 3. Press and release a Remote Button, (FIG. 2)—the Learn Code LED will stay on (stops blinking).
- 4. Press and release the same Remote Button again—the Learn Code LED will turn off.
- 5. Press and release the same Remote Button again—the Door Opener will run.

**NOTE**: Each opener must have its own assigned Remote Button. To program additional openers, repeat the steps above using a different Remote Button.

### B. For use with Intellicode® 2 Openers—

The button or buttons on your remote that you wish to use to operate **Intellicode® 2** openers, must be switched to the **Intellicode® 2** Operating Mode.

The **Intellicode® 2** Mode is indicated by a GREEN LED on the remote whenever a button is pressed (FIG. 2).

#### To shift to Intellicode® 2 mode:

- Press and hold the chosen Remote Button—A steady RED LED will be illuminated and after 10 seconds—a GREEN LED will also illuminate.
- 2. Release the button.
- 3. Press and release that same button again TWICE—the remote's LEDs will both turn off.
- 4. Press and release that same button again—the remote's GREEN LED will light while you press that button indicating it is now in *Intellicode*® 2 mode.

To program the remote to an opener:

- Press and hold the PROGRAM/SET (FIG. 1) button on your opener's powerhead for 2 seconds or until the round LED turns BLUE. When you release the button the BLUE LED will go out and the LONG LED will turn PURPLE.
- 2. Press and release the Remote Button you want to assign to that opener.
- Press and release that same button. After releasing the button the second time, the LEDs will both be off.
- 4. Press and release that same button again—the Door Opener will run.

# C. For use with Openers having a row of Code Switches (9 or 12 switches). (If you already have a working "code switch" remote, simply match your new

(If you already have a working "code switch" remote, simply match your new GenieMaster™ Remote switches to those on your existing remote and proceed to step 4.)(FIG.3)

### To operate a Code Switch equipped operator:

- 1. Open the opener's light lens in order to gain access to its row of Code Switches. These are 3 position switches (+, and 0).
- 2. Slide off the rear cover of the remote (FIG. 3).
- 3. Set the Code Switches positions in the remote to match those of the switches in the opener. (If you are working with a 9 switch operator, set the remote switches 10, 11 and 12 to the center or "0" position)
- 4. Locate the non-rolling code button label inside the Rear Cover (FIG. 3).
- Press the non-rolling code button B, C or D (FIG.3) that matches the appropriate code switch description on the label. The YELLOW LED next to the battery will begin flashing.
- 6. Press and release the Remote Button you want to assign to that opener—the GREEN LED on the remote will flash for approximately 2 seconds and stop.
- 7. **Pressing the same button again will operate the opener**—The RED LED on the remote will flash while the button is pressed.

# D. Replacing the Battery. (Programming will not be affected by battery replacement.)


- 1. Slide the Circuit Board Cover off the back of the remote (FIG. 3).
- 2. Slide the old battery toward the bottom of the remote and out.
- 3. Properly discard the old battery.
- 4. Slide a new (2032 size) battery into position and slide the Cover back on.


## E. Resetting the Remote


### To return a Remote Button to its original Intellicode® 1 mode:

- 1. Slide the Circuit Board Cover off (FIG. 3).
- 2. Press the DEFAULT button—the yellow LED will flash.
- 3. Press the Remote Button you wish to reprogram. Its now *Intellicode® 1* again.


FIG. 1 POWERHEADS (for various models)
Circle shows location of Learn Code Button and LED.











FOR HELP OR ANSWERS TO QUESTIONS, CALL 800-354-3643 or visit www.geniecompany.com